




Through-beam sensor receiver

OUE-HNKG

Article no longer available - archive entry



Receiver in upper lens

Product characteristics

Housing		rectangular
Dimensions	[mm]	28 x 16 x 51

Application

Function principle		Through-beam sensor
--------------------	--	---------------------

Electrical data

Operating voltage	[V]	10...55 DC
Current consumption	[mA]	20; ((24 V))
Protection class		II
Reverse polarity protection		yes

Outputs

Electrical design		NPN
Output function		light-on mode
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	140
Short-circuit protection		yes
Type of short-circuit protection		yes (non-latching)
Overload protection		yes

Monitoring range

Transmitter / receiver		receiver
Range	[m]	< 6
Range adjustable		yes

Operating conditions

Ambient temperature	[°C]	-25...80
Protection		IP 67



OU5009



Through-beam sensor receiver

OUE-HNKG

Tests / approvals		
EMC	EN 60947-5-2	
	EN 55011	class B
MTTF	[years]	672
Mechanical data		
Weight	[g]	0.155
Housing		rectangular
Dimensions	[mm]	28 x 16 x 51
Material		PPO modified
Lens material		glass
Displays / operating elements		
Display	Switching status	1 x LED, yellow
Accessories		
Items supplied	Angle bracket: 1, E20211	
Remarks		
Pack quantity	1 pcs.	
Electrical connection		
Cable: 2 m, PVC; 3 x 0.34 mm ²		
Connection		



Core colors :

- BN = brown
- BU = blue
- BK = black