

# Configuration summary

| Mat. no. | Description<br>Order code                | Quantity | Unit |
|----------|--|----------|------|
| 71008645 | Deltapilot S FMB70<br>FMB70-ACR1M12TKCAA | 1        | ST   |

|     |                                      |    |   |
|-----|--------------------------------------|----|---|
| 010 | Approval:                            | A  | Non-hazardous area  |
| 020 | Output; Operating:                   | C  | 4-20mA HART; inside   |
| 030 | Housing; Cover Sealing; Cable Entry: | R  | T17 316L hygiene IP66/68<br>NEMA6P;EPDM;M20 gland, T17 =<br>side cover              |
| 040 | Sensor Range; Sensor Overload Limit: | 1M | 4bar/400kPa/60psi/40mH2O/1600inH2<br>O<br>24bar/2.4MPa/350psi/240mH2O/9500i<br>nH2O |
| 050 | Calibration; Unit:                   | 1  | Sensor range; mbar/bar  |
| 060 | Membrane Material; Seal:             | 2  | AlloyC276; welded   |
| 070 | Process Connection:                  | TK | DRD 65mm PN25, 316L   |
| 090 | Fill Fluid:                          | C  | Synthetic oil (FDA)   |
| 100 | Additional Option 1:                 | A  | Not selected  |
| 110 | Additional Option 2:                 | A  | Not selected  |